

IN THE CLAIMS

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please **ADD** new claims 25 and 26 as follows.

Please **AMEND** claims 1, 5, 10, 12, 13, 15, 16, 17, 18, 23 and 24 as follows.

1. (CURRENTLY AMENDED) A method of transferring packets between a plurality of nodes including a first node, a second node, and a third node connected by a bus but not connected in a ring form, the method comprising:

- transferring a write packet from the first node to the second node;
- storing data to be written in a data portion of a packet addressed to the third node in the data portion of the write packet at the second node; and
- transferring the write packet from the second node to the third node.

2. (PREVIOUSLY PRESENTED) The packet transfer method according to claim 1, wherein the write packet comprises a blank data portion for storing the data.

3. (PREVIOUSLY PRESENTED) The packet transfer method according to claim 1, wherein the first node has information indicating that a plurality of the second nodes substantially simultaneously transfer packets to a plurality of the third nodes, and the write packet transferring comprises transferring a plurality of write packets to the plurality of the second nodes based on the information.

4. (ORIGINAL) The packet transfer method according to claim 1, wherein the write packet includes a header portion and a data portion, and wherein the data portion stores identification information indicating whether the data portion is blank.

5. (CURRENTLY AMENDED) ~~The packet transfer method according to claim 4~~
A method of transferring packets between a plurality of nodes including a first node, a second node, and a third node connected by a bus but not connected in a ring form, the method

comprising:

transferring a write packet from the first node to the second node;
storing data to be written in a data portion of a packet addressed to the third node in the
data portion of the write packet at the second node; and
transferring the write packet from the second node to the third node,
wherein the write packet transferring comprises transferring from the first node to
the second node a guide packet ~~to the second node storing~~ that stores guide information
indicating a state of the write packet, before the first node transfers the write packet to the
second node, and
wherein the data storing by the second node comprises writing ~~the guide~~
~~information to~~ as the guide information of the guide packet to indicate information indicating that
the data has been written to the write packet by the second node.

6. (PREVIOUSLY PRESENTED) The packet transfer method according to claim 1,
further comprising:

transferring a data packet from the first node to the second node;
processing the data stored in the data packet at the second node; and
transferring the data packet including the processed data to the third node, wherein the
write packet transferring is performed after the data packet transferring.

7. (PREVIOUSLY PRESENTED) The packet transfer method according to claim 1,
wherein the write packet transferring comprises transferring the write packet from the first node
to the second node at predetermined time periods.

8. (PREVIOUSLY PRESENTED) The packet transfer method according to claim 1,
further comprising padding the data stored in the write packet so that the data amount is
substantially same as the data storage capacity of the write packet.

9. (PREVIOUSLY PRESENTED) A method of transferring packets between a
plurality of connected nodes including a first node, a second node, and a third node, the first
node, the second node, and the third node not connected in a ring form, the method comprising:
transferring a first packet storing first data from the first node to the second node;
processing the first data stored in the first packet and temporarily storing the processed
first data at the second node;

transferring a second packet storing second data from the first node to the second node;
rewriting the second data stored in the second packet with the processed and
temporarily stored first data at the second node; and
transferring the second packet including the processed first data to the third node.

10. (CURRENTLY AMENDED) A packet transfer control circuit incorporated in a first node to transfer a packet to a second node, connected to the first node, wherein the packet includes a data portion for storing data, the control circuit comprising:

an identification circuit identifying whether the data portion of the packet is blank; and
a processor connected to the identification circuit and ~~writing~~determining that data can
be written to the data portion of the packet, when the data portion of the packet is blank
according to the identifying by the identification circuit, and transferring the packet to a third
node, wherein the first node, the second node, and the third node are not connected in a ring
form.

11. (PREVIOUSLY PRESENTED) The packet transfer control circuit according to
claim 10, wherein the processor pads the data stored in the packet until the data amount is
substantially the same as the data storage capacity of the data portion.

12. (CURRENTLY AMENDED) A packet transfer control circuit incorporated in a first node to transfer a packet to a second node and a third node, in which the first node, the second node, and the third node are not connected in a ring form, ~~wherein~~ the packet includes a data portion for storing data, ~~and wherein~~ the second node is downstream from the first node, and the third node is upstream from the first node, the control circuit comprising:

a processor retaining data addressed to the third node, and rewriting the data stored in the data portion of the packet, which is received by the first node from the second node, with to include the retained data addressed to the third node, when the data stored data in the data portion of the packet received from the second node is addressed to the third node.

13. (CURRENTLY AMENDED) A packet transfer control circuit incorporated in a first node to transfer a plurality of packets to a second node and a third node, the first node, the second node, and the third node not connected in a ring form, wherein each packet includes a data portion for storing data, the control circuit comprising:

a processor transferring a plurality of write packets, the data portion of which is blank, to

each of the second and third nodes based upon information indicating so that the second and third nodes substantially simultaneously store data in the data portion of the write packets received from the first node.

14. (PREVIOUSLY PRESENTED) The control circuit according to claim 13, wherein each write packet further include an identifier for storing information indicating whether the data portion of each write packet is blank.

15. (CURRENTLY AMENDED) ~~The control circuit according to claim 13~~ A packet transfer control circuit incorporated in a first node to transfer a plurality of packets to a second node and a third node, in which the first node, the second node, and the third node are not connected in a ring form and each packet includes a data portion for storing data, the control circuit comprising:

Cont
10'
a processor transferring a plurality of write packets, the data portion of which is blank, to each of the second and third nodes so that the second and third nodes substantially simultaneously store data in the data portion of the write packets received from the first node,

wherein the processor transfers to the second and third nodes a plurality of guide packets storing that store guide information indicating a state of the write packets before transferring the write packets from the first node to the second and third nodes, and

wherein the guide information written to the guide packets at the second and third nodes indicates that data has been written to the write packets by the second and third nodes, when the second and third nodes store the data in the data portion of the received-write packets received from the first node.

16. (CURRENTLY AMENDED) A packet transfer control circuit incorporated in a first node to transfer packets to a plurality of second and third nodes, in which the first, second, and third node and the plurality of second nodes are not connected in a ring form, ~~wherein and~~ each packet includes a data portion for storing data, the control circuit comprising:

a processor transferring to each second node a write packet, the data portion of which stores data, and then transferring another a further-write packet, the data portion of which is blank, wherein each second node stores data in the blank data portion and transfers the packet to the third nodes.

17. (CURRENTLY AMENDED) The control circuit according to claim 16, wherein the

other write packet further includes an identifier for storing information indicating whether the data portion is blank.

18. (CURRENTLY AMENDED) ~~The control circuit according to claim 16~~ A packet transfer control circuit incorporated in a first node to transfer packets to a plurality of second nodes, in which the first node and the plurality of second nodes are not connected in a ring form and each packet includes a data portion for storing data, the control circuit comprising:

a processor transferring to each second node a write packet, the data portion of which stores data, and then another write packet, the data portion of which is blank,

wherein each second node stores data in the blank data portion,

wherein the processor transfers to the second nodes guide packets that store a guide packet storing guide information indicating a state of the each write packet before transferring the each write packet from the first node to the second nodes, and

wherein the guide information written to the guide packet packets at the second nodes indicates whether data has been written to the each write packet by the second nodes, when each of the second nodes stores the data in the blank data portion of the each write packet received from the first node.

19. (ORIGINAL) A packet transfer control circuit of a first network node, comprising an input interface circuit for receiving a packet from a second network node connected to the first network node, the received packet being one of a normal packet type and a write packet type, and the received packet comprising at least a header portion and a data portion;

an input link layer processing circuit, connected to the input interface circuit, for receiving the received packet therefrom, reading the header portion of the packet to determine the packet type, and if the received packet is a normal packet, also determining an addressee of the packet;

an identification circuit, connected to the input link layer processing circuit, for receiving a write packet type of packet from the input link layer processing circuit, checking an identifier of the data portion of the write packet to determine whether the data portion of the write packet is blank and to determine an addressee of the write packet, wherein the identification circuit generates a control signal if the data portion is blank;

a processor, connected to the identification circuit and the input link layer processing circuit, wherein the input link layer processing circuit passes the received packet directly to the processor if the received packet is addressed to the first node and is a normal type packet,

wherein the processor receives the packet data from the identification circuit if the packet is a write type packet, and wherein the processor receives the control signal from the identification circuit and pads the data portion of the packet in order to fill the data portion of the packet when the control signal indicates that the data portion is blank;

a memory, connected to the processor, for storing the packet data processed by the processor;

an output link layer processing circuit, connected to the processor and to the input link layer processing circuit, for receiving the packet therefrom and preparing a transmission packet from the packet, wherein the input link layer processing circuit passes a normal type packet not addressed to the first node directly to the output link layer processing circuit; and

an output interface circuit, connected to the output link layer processing circuit, for receiving the transmission packet therefrom and transmitting the transmission packet over a bus to another node.

20. (ORIGINAL) The packet transfer control circuit of claim 19, wherein the packets are transferred between nodes over an IEEE 1394 compatible bus.

21. (ORIGINAL) The packet transfer control circuit of claim 19, further comprising:
an input physical layer processing circuit, connected between the input link layer processing circuit and the input interface circuit, for receiving the packets from the input interface circuit and transferring them to the input link layer processing circuit.

22. (ORIGINAL) The packet transfer control circuit of claim 21, further comprising:
an output physical layer processing circuit connected between the output link layer processing circuit and the output interface circuit, for transferring the transmission packet from the output link layer processing circuit to the output interface circuit.

23. (CURRENTLY AMENDED) A method of transferring packets between a plurality of nodes connected in a star form, the plurality of nodes including a first node, a second node, and a third node, the method comprising:
transferring a write packet from the first node to the second node;
storing data to be written in a data portion of a packet addressed to the third node in the data portion of the write packet at the second node; and
transferring the write packet from the second node to the third node.

24. (CURRENTLY AMENDED) A packet transfer control device incorporated in a first node to transfer a packet to a second node and a third node, in which the first node, the second node and the third node are connected in a star form and form; the packet ~~including~~includes a data portion for storing data, the device comprising:

an identification circuit identifying whether the data portion is blank; and

CBPT
p1
a processor connected to the identification circuit ~~for writing~~and determining that data can be written to the data portion of the packet, ~~if when~~ the data portion of the packet is blank according to the identifying by the identification circuit, and transferring the packet to the third node.

25. (NEW) The packet transfer method according to claim 1, wherein the data comprises image data.

26. (NEW) The packet transfer method according to claim 23, wherein the data comprises image data.
